




VARISPIN 4A

MULTI CENTRIFUGE

자주 사용하는 어플리케이션을 위한
앵글로터 전용 소형 원심분리기



● ● ● STANDARD SPECIFICATION



Max. RPM	4,000rpm
Max. RCF	2,075 xg
Max. Capacity	15ml x 8
Accel / Decel phase	≤60dB
Noise Level	99 min 59 sec or continuous
Set Time	From start / From set-up RPM
Time Count	10 memory
Program	Blue LCD
Display	400 to 4,000 RPM
RPM Range	RPM(RCF), Time, Program
Available Rotor Quantity	1
Power Supply	230V ± 10%, 50-60Hz, 1Phase
Power Consumption	150W
Dimension(W x D x H)	291 x 415.5 x 228mm (H:525mm with open lid)
Weight (without rotor)	14kg

● ● ● MAIN FEATURE

● 컴팩트한 구조

컴팩트한 디자인으로 실험실 내 공간활용성을 높였고, 15ml 튜브를 최대 8개까지 사용 가능하도록 용량을 최대화하였습니다.

● 튜브 사용 범위

10ml, 15ml 크기의 튜브 사용이 가능합니다.









● 높은 시인성의 LCD 스크린 사용

블루 LCD 스크린에 화이트 입력 값을 사용하여 가독성을 높였습니다. LCD 스크린 주변에 직관적인 아이콘 형태의 터치패드를 구성하였습니다.

● ● ● ORDER INFORMATION

	ITEM	DESCRIPTIONS	ORDER CODE
Main Body	VARISPIN 4A Set	VARISPIN 4A, with rotor AL815D, including 15ml stainless steel sleeves, 230V/50~60Hz	V4A-SET
	VARISPIN 4A	VARISPIN 4A, without rotor, 230V/50~60Hz	V4A-MB
Angle Rotor	AL815D	15ml x 8 fixed angle rotor with 15ml stainless steel sleeves (Max 4,000RPM)	V4A-AR1

● ● ● ORDER INFORMATION

AL815D	F15A-3	F15A-5							
									
Fixed Angle rotor $\angle 40^\circ$ 8 x 15ml Radius(mm) : 116									
Volume (ml)	3	5	10	15	15 Conical				
Number per rack / rotor	8	8	8	8	8				
Adaptor bore (mm)	13.5	13.5	18.0	18	18				
Max. height for use (mm)	120	142	131	131	131				
RPM	4,000	4,000	4,000	4,000	4,000				
Radius (mm)	97.4	114.3	116	116	110.2				
RCF	1,742	2,045	2,075	2,075	1,971				